




- 2000 W continuous program power capacity
- 100 mm (4 in) copper voice coil
- 35 - 1000 Hz response
- 94.5 dB sensitivity
- FEA optimized Neodymium magnet assembly
- Aluminium demodulating ring for very low distortion
- Double silicone spider with optimized compliance
- Ventilated voice coil gap for reduced power compression



## SPECIFICATIONS

Nominal Diameter	380 mm (15 in)
Nominal Impedance	8 Ω
Minimum Impedance	6 Ω
Nominal Power Handling	1000 W 2 hours test made with continuous pink noise signal within the range Fs-10Fs. Power calculated on rated minimum impedance. Loudspeaker in free air.
Continuous Power Handling	2000 W Power on Continuous Program is defined as 3 dB greater than the Nominal rating.
Sensitivity	94.5 dB Applied RMS Voltage is set to 2.83 V for 8 ohms Nominal Impedance.
Frequency Range	35 Hz - 1000 Hz
Voice Coil Diameter	100 mm (4 in)
Winding Material	Copper
Former Material	Glass Fibre
Winding Depth	27 mm (1.05 in)
Magnetic Gap Depth	11 mm (0.43 in)
Flux Density	1.25 T
Woofer Cone Treatment	TWP Waterproof Both Sides

## PARAMETERS

Thiele-Small parameters are measured after a high level 20 Hz sine wave preconditioning test.

Fs	36 Hz
Re	5.1 Ω
Qes	0.49
Qms	5
Qts	0.44
Vas	83 dm <sup>3</sup> (2.93 ft <sup>3</sup> )
Sd	855 cm <sup>2</sup> (132.5 in <sup>2</sup> )
η0	0.8 %
Xmax	10.5 mm
Xvar	14 mm
Mms	240 g
Bl	23 Tm
Le	1.6 mH
EBP	73 Hz

## DESIGN

Surround Shape	Roll
Cone Shape	Radial
Magnet Material	Neodymium Inside Slug
Spider	Double Silicone
Pole Design	T-Pole
Woofer Cone Treatment	TWP Waterproof Both Sides
Recommended Enclosure	160 dm <sup>3</sup> (5.65 ft <sup>3</sup> )
Recommended Tuning	29 Hz

## MOUNTING AND SHIPPING INFO

Overall Diameter	393 mm (15.5 in)
Bolt Circle Diameter	374 mm (14.7 in)
Baffle Cutout Diameter	354 mm (13.9 in)
Depth	189 mm (7.44 in)
Flange and Gasket Thickness	24 mm (0.94 in)
Air Volume Occupied by Driver	6 dm <sup>3</sup> (0.21 ft <sup>3</sup> )
Net Weight	8.8 kg (19.4 lb)
Shipping Units	1 pcs
Shipping Weight	10.1 kg (22.27 lb)
Shipping Box	425x425x224 mm (16.73x16.73x8.82 in)

## SERVICE KITS

LF recone-kits	RCK15BG1008
----------------	-------------