



- 60 W continuous program power capacity
- 1" horn throat diameter
- 36 mm (1.4 in) aluminum voice coil
- Titanium diaphragm
- 1500 - 18000 Hz response
- 105 dB sensitivity



SPECIFICATIONS

Driver mounted on B&C ME 45 horn.

Throat Diameter	25 mm (1 in)
Nominal Impedance	8 Ω
Minimum Impedance	7.4 Ω
Nominal Power Handling	30 W 2 hour test made with continuous pink noise signal within the range from the recommended crossover frequency to 20 kHz. Power calculated on rated minimum impedance.
Continuous Power Handling	60 W Power on Continuous Program is defined as 3 dB greater than the Nominal rating.
Sensitivity	105 dB Applied RMS Voltage is set to 2.83 V for 8 ohms Nominal Impedance.
Frequency Range	1.5 kHz - 18 kHz
Recommended Crossover	2.2 kHz 12 dB/oct. or higher slope high-pass filter.
Voice Coil Diameter	36 mm (1.4 in)
Winding Material	Aluminium
Inductance	0.14 mH
Flux Density	1.45 T
Diaphragm Material	Titanium

SERVICE KITS

HF replacement-diaphragm	MMD014TN8
--------------------------	-----------

MOUNTING AND SHIPPING INFO

Two M5 holes 180° on 76 mm (3 in) diameter Three M6 holes 120° on 57 mm (2.2 in) diameter

Overall Diameter	90 mm (3.5 in)
Depth	49 mm (2 in)
Net Weight	1 kg (2.2 lb)
Shipping Units	1 pcs
Shipping Weight	1.03 kg (2.27 lb)
Shipping Box	105x105x65 mm (4.13x4.13x2.56 in)