




- 1400 W continuous program power capacity
- 88 mm (3.5 in) aluminium voice coil
- 45 - 3000 Hz response
- 99 dB sensitivity
- Ventilated voice coil gap for reduced power compression
- Double silicone spider with optimized compliance
- Aluminum demodulating ring allows a very low distortion figure

The NDL88 series is perfectly balanced for the loudspeaker systems of today. Incorporating a high temperature neodymium magnet inside the 3.5" (88mm) voice coil reduces the amount of steel needed in the motor structure, saving cost and weight. Unexpected low frequency output and midrange extension to meet with almost any driver for two way applications is the hallmark of this new performance-oriented woofer line from B&C Speakers. Do more, with less, with the NDL88 series.



Model:	15NDL88	Configuration:	One Driver
Enclosure Type:	Box Refer.		
Impedance (Nominal):	4 Ω	QES	3
Rated Frequency (Hz):	45	Flux Area (cm²):	250.0
Frequency 90 dB (Hz):	45.0	Flux Length (cm):	14.3
Frequency 110 dB (Hz):	35.0		

### SPECIFICATIONS

Nominal Diameter	380 mm (15 in)
Nominal Impedance	4 Ω
Minimum Impedance	3.7 Ω
Nominal Power Handling	700 W 2 hours test made with continuous pink noise signal within the range Fs-10Fs. Power calculated on rated minimum impedance. Loudspeaker in free air.
Continuous Power Handling	1400 W Power on Continuous Program is defined as 3 dB greater than the Nominal rating.
Sensitivity	99 dB Applied RMS Voltage is set to 2 V for 4 ohms Nominal Impedance.
Frequency Range	45 Hz - 3000 Hz
Voice Coil Diameter	88 mm (3.5 in)
Winding Material	Aluminium
Former Material	Glass Fibre
Winding Depth	21.5 mm (0.85 in)
Magnetic Gap Depth	10 mm (0.39 in)
Flux Density	1.05 T
Woofer Cone Treatment	WP Waterproof Front Side

### PARAMETERS

Thiele-Small parameters are measured after a high level 20 Hz sine wave preconditioning test.

Fs	41 Hz
Re	3 Ω
Qes	0.29
Qms	7.5
Qts	0.28
Vas	154 dm <sup>3</sup> (5.44 ft <sup>3</sup> )
Sd	855 cm <sup>2</sup> (132.53 in <sup>2</sup> )
η0	3.5 %
Xmax	8 mm
Xvar	10 mm
Mms	102 g
Bl	16.5 Tm
Le	0.9 mH
EBP	141 Hz

### DESIGN

Surround Shape	Triple Roll
Cone Shape	Exponential
Magnet Material	Neodymium Inside Slug
Spider	Double Silicone
Pole Design	T-Pole
Woofer Cone Treatment	WP Waterproof Front Side
Recommended Enclosure	125 dm <sup>3</sup> (4.41 ft <sup>3</sup> )
Recommended Tuning	45 Hz

### MOUNTING AND SHIPPING INFO

Overall Diameter	393 mm (15.47 in)
Bolt Circle Diameter	374 mm (14.72 in)
Baffle Cutout Diameter	354 mm (13.94 in)
Depth	177 mm (6.97 in)
Flange and Gasket Thickness	13 mm (0.51 in)
Air Volume Occupied by Driver	3.5 dm <sup>3</sup> (0.12 ft <sup>3</sup> )
Net Weight	5.7 kg (12.57 lb)
Shipping Units	1 pcs
Shipping Weight	7 kg (15.43 lb)
Shipping Box	425x425x224 mm (16.73x16.73x8.82 in)

### SERVICE KITS

LF recone-kits	RCK15NDL884
----------------	-------------